



H03 VV-F

PVC insulated cord

RoHS

CROSS SECTION



Acc. to VDE 0285-525-2-11

APPLICATION

For connections subject to low mechanical loads, such as the connection of light electrical appliances (radios, lights, vacuum cleaners, kitchen appliances etc.). Not, however, suitable for heating and cooking appliances or outdoor use.

STRUCTURE

Conductor	Copper stranded wire, bare, flexible/cores concentrically stranded in layers, according to DIN VDE 0281 part 5
Cores	PVC insulation according to VDE 0207 part 4, colour-coded or labelled with imprinted digits according to VDE 0293
Outer sheath	PVC according to VDE 0207 part 5

SPECIAL FEATURES

Sheath colour
Black or white with inscription, additional colours on request

TECHNICAL DATA

Nominal voltage	300 V/300 V
Test voltage	2000 V
Insulation resistance	20 MΩ x km at 20°C
Operating temperature	-40°C to +70°C
Max. operating temperature	+70°C
Min. installation temperature	-5°C
Max. installation temperature	+70°C
Min. bending radius	10 x cable diameter

Product description	Cu weight	Outer Ø (mm)	Weight (kg/km)	Product number
H03VV-F 2X0.75 White	14.4	5.6	46	1041103
H03VV-F 2X0.75 Black	14.4	5.6	46	1041106
H03VV-F 3G0.75 White	21.6	6.0	55	1041109
H03VV-F 3G0.75 Black	21.6	6.0	55	1041112
H03VV-F 4G0.75 White	29.0	6.5	69	1041115
H03VV-F 4G0.75 Black	29.0	6.5	69	1041118